



## **Clear Penetrating Lubricant**

SWEPCO 801 Clear Penetrating Lubricant is a premium quality penetrating oil and lubricant. Use it for loosening frozen

and corroded bolts, nuts, screws, clamps and other

threaded parts. Also good for pins and hinges and other parts that need disassembly. Just spray it on and let it go to work dissolving and loosening rust, corrosion and crud of all kinds. Super fast penetration means more work gets done with less wait time. And the clear formula means less clean-up. After disassembly and reassembly, spray parts to help prevent future rust and corrosion.

## KEY BENEFITS

- Convenient aerosol spray any way even straight up
- Penetrates, loosens and dissolves rust, corrosion, paint, dirt, dope, grease
- Loosens frozen/corroded parts fast with less wait time
- Helps protect against future rust and corrosion
- Clear formula makes clean-up easier
- Works as a protective lubricant too
- Perfect for screws, nuts, bolts, allen screws, chains, pins, hinges, clamps and threaded parts of all kinds

## Typical Physical Properties:

Density, @ 60°F, Lbs./Gal. (kg./L.) Viscosity	7.16 (0.86)
with solvents, cSt @ 40°C without solvents, cSt @ 40°C	
without solvents cSt @ 100°C Pour Point, °F (°C), ASTM D-97 VOC, %	45 (-43)
Color	
Typical Performance Properties:	
Copper Strip Corrosion, ASTM D-130 Rust Test, ASTM D-665 Seal Compatibility	pass

Seal Compatibilitypass
Product Operating Temperature Range
Intermittent, °F (°C)
Continuous, °F (°C)40 to 200 (-40 to 93)
Container Operating Temperature Range, °F (°C) 40 to 100 (4 to 38)

WARNING -- FLAMMABLE AEROSOL MIXTURE. STORE AT TEMPERATURES BELOW 120°F (49°C). DO NOT EXPOSE TO OPEN FLAME OR OTHER SOURCES OF IGNITION WHEN SPRAYING.



Fort Worth, Texas • Phone: (800)359-5823 or (817)332-2336 • Fax: (817)348-7237 • Web: www.swepcolube.com Southwestern Petroleum Europe • Southwestern Petroleum Canada