

SDS Revision Date: 04/11/2024

Section 1. Identification

Product identifier

Product Identity 123 Ultra EP Multi-Service Grease

Other means of identification 123

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name Southwestern Petroleum Lubricants LLC

3401 Quorum Drive, Suite 360

Fort Worth, Texas 76137

Emergency

24 hour Emergency

734 930-0009

Telephone No.

Customer Service: Emergency numbers call Chemtrec 24/7 USA and Canada 1-

800-424-9300 or 1-703-527-3887

Section 2. Hazard(s) identification

This SDS is aligned with the Workplace Hazardous Materials Information System (WHMIS) and with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Classification of the substance or mixture

The substance is not classified according to the WHMIS regulations.

Label elements



SDS Revision Date: 04/11/2024

The substance is not classified according to the WHMIS regulations.

[Prevention]:

No GHS prevention statements

[Response]:

No GHS response statements

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

ATE ({Orallab}) {Oral-Range} mg/kg. {UNKToxOral} {unkstate}

ATE ({Dermlab}) {Derm-Range} mg/kg. {UNKToxDerm} {unkstate}

ATE ({inhlab}) {inh-range} {noDPDCat}. {UNKToxInh} {unkstate}

2.3. Other hazards

This product contains no PBT/vPvB chemicals.

This product contains no endocrine disrupting chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated light naphthenic CAS Number: 64742-53-6 Synonyms: Distillates (petroleum), hydrotreated light naphthenic; Baseoil-unspecified	10 - 30	Not Classified	
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified CAS Number: 64742-52-5 Synonyms: Distillate (petroleum) hydrotreated heavy naphthenic, Polymer Binders and Adhesive	10 - 30	Not Classified	
Calcium carbonate CAS Number: 471-34-1 Synonyms: Calcium carbonate	3 - 7	Not Classified	

The actual concentration or concentration range is withheld as a trade secret.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.



SDS Revision Date: 04/11/2024

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position

and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids

apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or

use a recognized skin cleanser.

Ingestion DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously.

If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse

mouth thoroughly. Get medical attention.

Most important symptoms and effects, both acute and delayed

Overview If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Treat symptomatically. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.



SDS Revision Date: 04/11/2024

Special hazards arising from the substance or mixture

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Local authorities should be advised if significant spillages cannot be contained.

Section 7. Handling and storage

Precautions for safe handling

swepco

Safety Data Sheet 123 Ultra EP Multi-Service Grease

SDS Revision Date: 04/11/2024

Handle containers carefully to prevent damage and spillage.

Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Storage Temperature: -50 - 50C (-58 - 122F)

For containers or container linings, use mild steel or high density polyethylene.

Do not use PVC.

Incompatible materials: No available information

See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
471-34-1	Calcium carbonate	ACGIH	No Established Limit
		Alberta	10 mg/m ³ TWA
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	10 mg/m³TWA (listed under Limestone) 20
			mg/m³STEL (listed under Limestone)
		Nunavut	10 mg/m³TWA (listed under Limestone) 20
			mg/m³STEL (listed under Limestone)
		Ontario	No Established Limit



SDS Revision Date: 04/11	/2024
--------------------------	-------

CAS No.	Ingredient	Source	Value
		Prince Edward Island	No Established Limit
		Quebec	10 mg/m³TWAEV (total dust)
		Saskatchewan	10 mg/m³TWA (listed under Limestone) 20
			mg/m³STEL (listed under Limestone)
		Yukon	30 mppcf TWA; 10 mg/m³TWA 20 mg/m³STEL
64742-	Distillates (petroleum), hydrotreated heavy	ACGIH	No Established Limit
52-5	naphthenic; Baseoil-unspecified	Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
64742-	Distillates (petroleum), hydrotreated light	ACGIH	No Established Limit
53-6	naphthenic	Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must

use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Skin protection is not required under normal conditions of use. Oil

impervious gloves and oil impermeable apron recommended.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any

vapour below occupational exposure limits suitable respiratory protection



SDS Revision Date: 04/11/2024

must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking,

smoking or using toilet. Promptly remove soiled clothing and wash

thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Lubricating Grease

ColorThick BlueOdourNone to Mild.

Melting point / freezing point 300C

Initial boiling point and boiling rangeNo available informationFlammability (solid, gas)No available information

Upper/lower flammability or explosive limits Lower Explosive Limit: 1.0 Upper Explosive Limit: 9.0

Flash Point °F °C, Test method: (Open

Auto-ignition temperature 330C

Decomposition temperatureNo available information

pH 8.0

Viscosity (cSt)

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

No available information

No available information

Vapour pressure (Pa)No available informationRelative Density0.92

Vapour Density No available information

Evaporation rate (Ether = 1) Nil **VOC Content** 000

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity



SDS Revision Date: 04/11/2024

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

No available information

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates (petroleum), hydrotreated light	> 5,000.00, Rat -	> 5,000.00, Rabbit -	No data	No data	No data
naphthenic - (64742-53-6)	Category: NA	Category: NA	available.	available.	available.
Distillates (petroleum), hydrotreated heavy	> 5,000.00, Rat -	No data available.	No data	5.70, Rat -	No data
naphthenic; Baseoil-unspecified - (64742-52-5)	Category: NA		available.	Category: NA	available.
Calcium carbonate - (471-34-1)	>2,000.00, Rat -	>2,000.00, Rat -	No data	No data	No data
	Category: 5	Category: 5	available.	available.	available.



SDS Revision Date: 04/11/2024

Carcinogen Data

CAS No.	Ingredient	Source	Value
471-34-1	Calcium carbonate	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3:
			No; Group 4: No;
		ACGIH	No Established Limit
64742-52-	Distillates (petroleum), hydrotreated heavy naphthenic;	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3:
5	Baseoil-unspecified		No; Group 4: No;
		ACGIH	No Established Limit
64742-53-	Distillates (petroleum), hydrotreated light naphthenic	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3:
6			No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed::

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Treat symptomatically.

Section 12. Ecological information



SDS Revision Date: 04/11/2024

Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	No data available.	No data available.	No data available.
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00, Scenedesmus subspicatus
Calcium carbonate - (471-34-1)	101.00, Oncorhynchus mykiss	101.00, Daphnia magna	No data available.

Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

Bioaccumulative potential

Contains components with the potential to bioaccumulate.

Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



SDS Revision Date: 04/11/2024

Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
	•	• •	
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper	Not Regulated	Not Regulated	Not Regulated
shipping name			
Transport hazard	TDG Hazard Class: Not	IMDG: Not Applicable	Air Class: Not
class(es)	Applicable	Sub Class: Not	Applicable
	Sub Class: Not Applicable	Applicable	Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: No;

Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

9,10-Anthracenedione, 1,4-diamino-, N,N'-mixed 2-ethylhexyl and Me and pentyl derivs.

Calcium carbonate



SDS Revision Date: 04/11/2024

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified

Distillates (petroleum), hydrotreated light naphthenic

Molybdenum, N,N-bis(C11-14-branched and linear alkyl)carbamodithioate oxo thioxo complexes

Naphtha (petroleum), heavy aromatic

Water

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information

SDS Revision Date

04/11/2024

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

Not Applicable

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws,



Safety Data Sheet SDS Revision Date: 04/11/2024 123 Ultra EP Multi-Service Grease

regulations, and orders

End of Document