



## 1. Identification

### 1.1. Product identifier

**Product Identity** 165 MolyXP Universal Extreme Pressure Grease  
**Alternate Names** 165

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** See Technical Data Sheet.

### 1.3. Details of the supplier of the safety data sheet

**Company Name** Southwestern Petroleum Lubricants LLC  
3401 Quorum Drive, Suite 360  
Fort Worth, Texas 76137

### Emergency

**24 hour Emergency Telephone No.** 734 930-0009  
**Customer Service: Southwestern Petroleum Lubricants LLC** Emergency numbers call Chemtrec 24/7 USA and Canada 1-800-424-9300 or 1-703-527-3887

## 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

No applicable GHS categories.

### 2.2. Label elements

No applicable GHS categories.

#### [Prevention]:

No GHS prevention statements

#### [Response]:

No GHS response statements

#### [Storage]:

No GHS storage statements

#### [Disposal]:

No GHS disposal statements

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillate (petroleum) hydrotreated heavy naphthenic CAS Number: 0064742-52-5	50 - 75	Asp. Tox. 1;H304	----
Distillates (petroleum), hydrotreated light naphthenic CAS Number: 0064742-53-6	25 - 50	Asp. Tox. 1;H304	----
Polybutene CAS Number: 0009003-29-6	10 - 25	Not Classified	----
Graphite CAS Number: 0007782-42-5	1 - 5	Not Classified	----

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

\*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

### Section 4. First aid measures

#### 4.1. Description of first aid measures

##### General

In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

##### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

##### Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

##### Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

##### Ingestion

DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### Overview

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact

dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

## **Section 5. Fire-fighting measures**

### **5.1. Extinguishing media**

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

### **5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

### **5.3. Advice for fire-fighters**

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

**ERG Guide No.**            ----

## **Section 6. Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### **6.2. Environmental precautions**

Do not allow spills to enter drains or waterways.

### **6.3. Methods and material for containment and cleaning up**

Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Local authorities should be advised if significant spillages cannot be contained.

## **Section 7. Handling and storage**

### **7.1. Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.

Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

This material has the potential to be a static accumulator. Proper grounding and bonding procedures should

be used during all bulk transfer operations.

Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Storage Temperature: -50 - 50C ( -58 - 122F)

For containers or container linings, use mild steel or high density polyethylene.

Do not use PVC.

Incompatible materials: Strong oxidizing agents and acids.

Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

### 7.3. Specific end use(s)

No available information

## Section 8. Exposure controls / personal protection

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0007782-42-5	Graphite	OSHA	TWA 15 mg/m3 TWA 15 mppcf
		ACGIH	TWA: 2 mg/m3
		NIOSH	TWA 2.5 mg/m3 (resp)
0009003-29-6	Polybutene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

### 8.2. Exposure controls

#### Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

#### Eyes

Protective safety glasses recommended

#### Skin

Skin protection is not required under normal conditions of use. Oil impervious gloves and oil impermeable apron recommended.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

## Section 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical State</b>	Lubricating Grease
<b>Color</b>	Semi Solid Black, viscous gel
<b>Odor</b>	None
<b>Odor threshold</b>	No available information
<b>pH</b>	7.8
<b>Melting point / freezing point</b>	315 C
<b>Initial boiling point and boiling range</b>	No available information
<b>Flash Point</b>	°F °C, Test method: (Open/Close cup)
<b>Evaporation rate (Ether = 1)</b>	Nil
<b>Flammability (solid, gas)</b>	No available information
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 0.9 <b>Upper Explosive Limit:</b> 7.0
<b>Vapor pressure (Pa)</b>	No available information
<b>Vapor Density</b>	>5
<b>Relative Density</b>	0.95
<b>Solubility in Water</b>	Not miscible in water.
<b>Partition coefficient n-octanol/water (Log Kow)</b>	No available information
<b>Auto-ignition temperature</b>	330 C
<b>Decomposition temperature</b>	No available information
<b>Viscosity (cSt)</b>	No available information
<b>VOC Content</b>	0.0001

### 9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

## Section 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No available information

### 10.4. Conditions to avoid

Excessive heat and open flame.

### 10.5. Incompatible materials

Strong oxidizing agents and acids.

### 10.6. Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

## Section 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Polybutene - (9003-29-6)	> 10,000, Rat - Category: NA	No data available	No data available	No data available	No data available
Graphite - (7782-42-5)	> 2,000.00, Rat - Category: 4	No data available	No data available	> 2,000.00, Rat - Category: NA	No data available

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0007782-42-5	Graphite	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0009003-29-6	Polybutene	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable

Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## Section 12. Ecological information

### 12.1. Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	Not Available	Not Available	Not Available
Polybutene - (9003-29-6)	> 10,000, Leuciscus idus	101.00, Daphnia magna	101.00 (72 hr), Pseudokirchneriella subcapitata
Graphite - (7782-42-5)	100.00, Danio rerio	> 100.00, Daphnia magna	> 100.00 (72 hr), Pseudokirchnerella subcapitata

### 12.2. Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

### 12.3. Bioaccumulative potential

Contains components with the potential to bioaccumulate.

### 12.4. Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No available information

## Section 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## Section 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	Not Regulated	Not Regulated	Not Regulated
<b>14.2. UN proper shipping name</b>	Not Regulated	Not Regulated	Not Regulated
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>IMDG:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> Not Applicable <b>Sub Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No;		
<b>14.6. Special precautions for user</b>	No available information		

## Section 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

**Toxic Substance Control Act ( TSCA)** All components of this material are either listed or exempt from listing on the TSCA Inventory.

### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 Label Warning:**

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

<b>Chemical Name (CAS Number)</b>	<b>US TSCA</b>	<b>Australia AICS</b>	<b>Korea ECL</b>	<b>EU EINECS</b>	<b>EU ELINCS</b>	<b>EU SVHC</b>	<b>EN NLP</b>	<b>Mexico INSQ</b>
Distillate (petroleum) hydrotreated heavy naphthenic (0064742-52-5)	Yes	Yes	Yes	Yes	No	No	No	Yes
Distillates (petroleum), hydrotreated light naphthenic (0064742-53-6)	Yes	Yes	Yes	Yes	No	No	No	No
Polybutene (0009003-29-6)	Yes	Yes	Yes	No	No	No	Yes	Yes
Graphite (0007782-42-5)	Yes	Yes	Yes	Yes	No	No	No	Yes

<b>Chemical Name (CAS Number)</b>	<b>China IECSC</b>	<b>Japan ENCS</b>	<b>Japan ISHL</b>	<b>Japan PDSCL</b>	<b>Japan PRTR 1</b>	<b>Japan PRTR 2</b>	<b>Philippines PICCS</b>	<b>New Zealand NZIOC</b>
Distillate (petroleum) hydrotreated heavy naphthenic (0064742-52-5)	Yes	No	No	No	No	No	Yes	Yes
Distillates (petroleum), hydrotreated light naphthenic (0064742-53-6)	Yes	No	No	No	No	No	Yes	Yes

Polybutene (0009003-29-6)	Yes	Yes	No	No	No	No	Yes	Yes
Graphite (0007782-42-5)	Yes	No	No	No	No	No	Yes	Yes

<b>Section 16. Other information</b>
--------------------------------------

**SDS Revision Date**    01/25/2024

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

End of Document