



**Safety Data Sheet**  
**201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**

**Section 1. Identification**

**Product identifier**

**Product Identity** 201 Multi-Purpose Gear Lube  
**Other means of identification** 201

**Relevant identified uses of the substance or mixture and uses advised against**

See Technical Data Sheet.

**Details of the supplier of the safety data sheet**

**Company Name** Southwestern Petroleum Lubricants LLC  
3401 Quorum Drive, Suite 360  
Fort Worth, Texas 76137

**Emergency**

**24 hour Emergency Telephone No.** 734 930-0009

**Customer Service:**

Emergency numbers call Chemtrec 24/7 USA and Canada 1-800-424-9300 or 1-703-527-3887

**Section 2. Hazard(s) identification**

This SDS is aligned with the Workplace Hazardous Materials Information System (WHMIS) and with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

**Classification of the substance or mixture**

The substance is not classified according to the WHMIS regulations.

**Label elements**



Safety Data Sheet  
201 Multi-Purpose Gear Lube

SDS Revision Date: 07/2/2024

The substance is not classified according to the WHMIS regulations.

**[Prevention]:**

No GHS prevention statements

**[Response]:**

No GHS response statements

**[Storage]:**

No GHS storage statements

**[Disposal]:**

No GHS disposal statements

**Other hazards**

This product contains no PBT/vPvB chemicals.

This product contains no endocrine disrupting chemicals.

**Section 3. Composition/information on ingredients**

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated heavy naphthenic; Base oil-unspecified CAS Number: 64742-52-5 Synonyms: Distillate (petroleum) hydrotreated heavy naphthenic, Polymer Binders and Adhesive	65 - 85	Not Classified	----
Distillates Hydrotreated Heavy Paraffin CAS Number: 64742-54-7 Synonyms: Distillates (petroleum), hydrotreated heavy paraffinic; Base oil-unspecified	7 - 13	Not Classified	----
Polybutene CAS Number: 9003-29-6 Synonyms: Polybutene	7 - 13	Asp. Tox. 1;H304 Skin Irrit. 2;H315	----

The actual concentration or concentration range is withheld as a trade secret.

\*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.



#### Section 4. First aid measures

##### Description of first aid measures

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

##### Most important symptoms and effects, both acute and delayed

**Overview** Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

#### Section 5. Fire-fighting measures

##### Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Unsuitable extinguishing media: Do not use; water jet.



**Special hazards arising from the substance or mixture**

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

**Advice for fire-fighters**

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

**Section 6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).  
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

**Environmental precautions**

Do not allow spills to enter drains or waterways.

**Methods and material for containment and cleaning up**

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.  
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

**Section 7. Handling and storage**

**Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.



**Safety Data Sheet  
201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**

See section 2 for further details. - [Prevention]:

**Conditions for safe storage, including any incompatibilities**

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

**Specific end use(s)**

No available information

**Section 8. Exposure controls / personal protection**

**Control parameters**

**Exposure**

CAS No.	Ingredient	Source	Value
9003-29-6	Polybutene	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
Yukon	No Established Limit		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic; Base oil-unspecified	ACGIH	No Established Limit
		Alberta	No Established Limit



**Safety Data Sheet**  
**201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**

CAS No.	Ingredient	Source	Value
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
		64742-54-7	Distillates Hydrotreated Heavy Parrafin
Alberta	No Established Limit		
British Columbia	No Established Limit		
Manitoba	No Established Limit		
New Brunswick	No Established Limit		
Newfoundland and Labrador	No Established Limit		
Nova Scotia	No Established Limit		
Northwest Territories	No Established Limit		
Nunavut	No Established Limit		
Ontario	No Established Limit		
Prince Edward Island	No Established Limit		
Quebec	No Established Limit		
Saskatchewan	No Established Limit		
Yukon	No Established Limit		

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup>OSHA PEL and 5 mg/m<sup>3</sup>ACGIH.



**Safety Data Sheet**  
**201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**

**Exposure controls**

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

**Eyes** Protective safety glasses recommended

**Skin** Avoid skin contact. Protective gloves recommended.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved using local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

**Section 9. Physical and chemical properties**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid
<b>Color</b>	Thick Blue
<b>Odour</b>	Mild Petroleum
<b>Melting point / freezing point</b>	No available information
<b>Initial boiling point and boiling range</b>	No available information
<b>Flammability (solid, gas)</b>	No available information
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:0.9</b> <b>Upper Explosive Limit:7.0</b>
<b>Flash Point</b>	°F °C, Test method: (Open cup)
<b>Auto-ignition temperature</b>	260C
<b>Decomposition temperature</b>	No available information
<b>pH</b>	No available information
<b>Viscosity (cSt)</b>	No available information
<b>Solubility in Water</b>	No available information
<b>Partition coefficient n-octanol/water (Log Kow)</b>	No available information
<b>Vapour pressure (Pa)</b>	No available information
<b>Relative Density</b>	0.9



**Safety Data Sheet**  
**201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**

<b>Vapour Density</b>	>5
<b>Evaporation rate (Ether = 1)</b>	nil
<b>VOC Content</b>	0.00001

**Other information**

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

**Section 10. Stability and reactivity**

**Reactivity**

Hazardous Polymerization will not occur.

**Chemical stability**

Stable under normal circumstances.

**Possibility of hazardous reactions**

No available information

**Conditions to avoid**

Excessive heat and open flame.

**Incompatible materials**

Strong oxidizing agents and acids.

**Hazardous decomposition products**

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

**Section 11. Toxicological information**

**Acute toxicity**

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis.





**Safety Data Sheet  
201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**

Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates (petroleum), hydrotreated heavy naphthenic; Base oil-unspecified - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	5.70, Rat - Category: NA	No data available.
Distillates Hydrotreated Heavy Paraffin - (64742-54-7)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Polybutene - (9003-29-6)	> 10,000, Rat - Category: NA	No data available.	No data available.	No data available.	No data available.

**Carcinogen Data**

CAS No.	Ingredient	Source	Value
9003-29-6	Polybutene	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic; Base oil-unspecified	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
64742-54-7	Distillates Hydrotreated Heavy Paraffin	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable



Safety Data Sheet  
201 Multi-Purpose Gear Lube

SDS Revision Date: 07/2/2024

Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

**Symptoms and effects, both acute and delayed::**

Treat symptomatically.

**Section 12. Ecological information**

**Toxicity**

No additional information is provided for this product. See Section 3 for chemical specific data.

**Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates (petroleum), hydrotreated heavy naphthenic; Base oil-unspecified - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00, Scenedesmus subspicatus
Distillates Hydrotreated Heavy Paraffin - (64742-54-7)	101.00, Pimephales promelas	> 10,000, Daphnia magna	100.00, Pseudokirchneriella subcapitata
Polybutene - (9003-29-6)	> 10,000, Leuciscus idus	101.00, Daphnia magna	101.00, Pseudokirchneriella subcapitata

**Persistence and degradability**

There is no data available on the preparation itself.

**Bioaccumulative potential**

No available information

**Mobility in soil**



No available information

**Results of PBT and vPvB assessment**

This product contains no PBT/vPvB chemicals.

**Other adverse effects**

No available information

**Section 13. Disposal considerations**

**Waste treatment methods**

Observe all federal, provincial and local regulations when disposing of this substance.

**Section 14. Transport information**

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	<b>TDG (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>UN number</b>	Not Regulated	Not Regulated	Not Regulated
<b>UN proper shipping name</b>	Not Regulated	Not Regulated	Not Regulated
<b>Transport hazard class(es)</b>	<b>TDG Hazard Class:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>IMDG:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> Not Applicable <b>Sub Class:</b> Not Applicable
<b>Packing group</b>	Not Applicable	Not Applicable	Not Applicable

**Environmental hazards**

Marine Pollutant: No;

**Special precautions for user**

No available information

**Section 15. Regulatory information**



**Safety Data Sheet**  
**201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**



This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

**Canadian Domestic Substance List (DSL):**

9,10-Anthracenedione, 1,4-diamino-, N,N'-mixed 2-ethylhexyl and Me and pentyl derivs.

Distillates (petroleum), hydrotreated heavy naphthenic; Base oil-unspecified

Distillates Hydrotreated Heavy Parrafin

Lubricating oils, petroleum, hydrotreated spent

Naphtha (petroleum), heavy aromatic

Polybutene

Polyisobutylene

**Canadian Non-Domestic Substance List (NDSL):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



**SDS Revision Date**

07/2/2024

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.



**Safety Data Sheet**  
**201 Multi-Purpose Gear Lube**

**SDS Revision Date: 07/2/2024**

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

**End of Document**