



Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Section 1. Identification

Product identifier

Product Identity 710 Maximum Performance Synthetic ATF
Other means of identification 710

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name Southwestern Petroleum Lubricants LLC
3401 Quorum Drive, Suite 360
Fort Worth, Texas 76137

Emergency
24 hour Emergency 734 930-0009
Telephone No.

Customer Service: Emergency numbers call Chemtrec 24/7 USA and Canada 1-800-424-9300 or 1-703-527-3887

Section 2. Hazard(s) identification

This SDS is aligned with the Workplace Hazardous Materials Information System (WHMIS) and with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Classification of the substance or mixture

The substance is not classified according to the WHMIS regulations.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



Label elements

Warning

The substance is not classified according to the WHMIS regulations.

[Prevention]:

No GHS prevention statements

[Response]:

P301+312 IF SWALLOWED: Call a POISON CENTER, doctor or physician if you feel unwell.

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does NOT contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the US EPA PFASMASTER combined list of PFAS chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates Hydrotreated Heavy Paraffin CAS Number: 64742-54-7 Synonyms: Distillates (petroleum), hydrotreated heavy paraffinic; Base Oil-unspecified	65 - 85	Not Classified	----



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand of Lubrication Engineers, Inc.



Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1-Decene, homopolymer, hydrogenated CAS Number: 68037-01-4 Synonyms: Dec-1-ene, homopolymer, hydrogenated	7 - 13	Asp. Tox. 1;H304	----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview No chronic toxicity or long-term toxicity information available. Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents more than the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full-face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Sweepco® is an affiliated brand of Lubrication Engineers, Inc.



Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.
 See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.
 See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
64742-54-7	Distillates Hydrotreated Heavy Paraffin	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Sweepco® is an affiliated brand of Lubrication Engineers, Inc.



CAS No.	Ingredient	Source	Value
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
68037-01-4	1-Decene, homopolymer, hydrogenated	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
Yukon	No Established Limit		

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved using local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties
--



Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Information on basic physical and chemical properties

Physical State	Liquid
Color	Pale Amber
Odor	None
Odor threshold	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	ASTM D 2892
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 0.8 Upper Explosive Limit: 7.0
Flash Point	Open Cup
Auto-ignition temperature	No available information
Decomposition temperature	No available information
pH	7
Viscosity (cSt)	ASTM D445 at 40C
Solubility in Water	Non-Emulsifier
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapour pressure (Pa)	No available information
Relative Density	0.844
Vapour Density	>3
Evaporation rate (Ether = 1)	Nil
VOC Content	None

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Sweepco® is an affiliated brand of Lubrication Engineers, Inc.



Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents more than the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates Hydrotreated Heavy Paraffin - (64742-54-7)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
1-Decene, homopolymer, hydrogenated - (68037-01-4)	> 5,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available.	4,800.00, Rat - Category: NA	No data available.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand of Lubrication Engineers, Inc.



Carcinogen Data

CAS No.	Ingredient	Source	Value
64742-54-7	Distillates Hydrotreated Heavy Paraffin	IARC	No
		ACGIH	No Established Limit
68037-01-4	1-Decene, homopolymer, hydrogenated	IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Ingestion

May be harmful if swallowed.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepeco® is an affiliated brand of Lubrication Engineers, Inc.



Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates Hydrotreated Heavy Paraffin - (64742-54-7)	101.00, Pimephales promelas	> 10,000, Daphnia magna	100.00, Pseudokirchneriella subcapitata
1-Decene, homopolymer, hydrogenated - (68037-01-4)	No data available.	No data available.	No data available.

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper	Not Regulated	Not Regulated	Not Regulated



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



shipping name

Transport hazard class(es)	Class: Not Applicable Sub Class: Not Applicable	Class: Not Applicable Sub Class: Not Applicable	Class: Not Applicable Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

IMDG Marine Pollutant: No;
Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

1-Decene, homopolymer, hydrogenated

Distillates Hydrotreated Heavy Parrafin

PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS,

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information

SDS Revision Date

27 January, 2026



Swepeco® is an affiliated brand
of Lubrication Engineers, Inc.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

End of Document