



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



Section 1. Identification

Product identifier

Product Identity 710 Maximum Performance Synthetic ATF
Other means of identification 710

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name Southwestern Petroleum Lubricants LLC
3401 Quorum Drive, Suite 360
Fort Worth, Texas 76137

Emergency
24 hour Emergency 734 930-0009
Telephone No.

Customer Service: Emergency numbers call Chemtrec 24/7 USA and Canada 1-800-424-9300 or 1-703-527-3887

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA’s Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

The substance is not classified according to the OSHA Hazcom or WHMIS regulations.

Label elements



Swepco® is an affiliated brand of Lubrication Engineers, Inc.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Warning

The substance is not classified according to the OSHA Hazcom or WHMIS regulations.

[Prevention]:

No GHS prevention statements

[Response]:

P301+312 IF SWALLOWED: Call a POISON CENTER, doctor or physician if you feel unwell.

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does NOT contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the US EPA PFASMASTER combined list of PFAS chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates Hydrotreated Heavy Paraffin CAS Number: 64742-54-7 Synonyms: Distillates (petroleum), hydrotreated heavy paraffinic; Base Oil-unspecified	65 - 85	Not Classified	No data available
1-Decene, homopolymer, hydrogenated	7 - 13	Aspiration hazard, category	



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand of Lubrication Engineers, Inc.



Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
CAS Number: 68037-01-4 Synonyms: Dec-1-ene, homopolymer, hydrogenated		1;H304	No data available

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview No chronic toxicity or long-term toxicity information available. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents more than the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full-face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.
See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
64742-54-7	Distillates Hydrotreated Heavy Paraffin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
68037-01-4	1-Decene, homopolymer, hydrogenated	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit



Swepco® is an affiliated brand of Lubrication Engineers, Inc.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved using local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Pale Amber
Odor	None
Odor threshold	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	ASTM D 2892
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 0.8 Upper Explosive Limit: 7.0
Flash Point	Open Cup
Auto-ignition temperature	No available information



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



Decomposition temperature	No available information
pH	7
Viscosity (cSt)	ASTM D445 at 40C
Solubility in Water	Non-Emulsifier
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	No available information
Relative Density	0.844
Vapor Density	>3
Evaporation rate (Ether = 1)	Nil
VOC Content	None

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity



Swepco® is an affiliated brand of Lubrication Engineers, Inc.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates Hydrotreated Heavy Paraffin - (64742-54-7)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
1-Decene, homopolymer, hydrogenated - (68037-01-4)	> 5,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available.	4,800.00, Rat - Category: NA	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
64742-54-7	Distillates Hydrotreated Heavy Paraffin	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
68037-01-4	1-Decene, homopolymer, hydrogenated	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand of Lubrication Engineers, Inc.



Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Ingestion May be harmful if swallowed.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates Hydrotreated Heavy Paraffin - (64742-54-7)	101.00, Pimephales promelas	> 10,000, Daphnia magna	100.00, Pseudokirchneriella subcapitata
1-Decene, homopolymer, hydrogenated - (68037-01-4)	No data available.	No data available.	No data available.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.



Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
Transport hazard class(es)	Class: Not Applicable Sub Class: Not Applicable	Class: Not Applicable Sub Class: Not Applicable	Class: Not Applicable Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

IMDG Marine Pollutant: No;
Special precautions for user



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand of Lubrication Engineers, Inc.



No available information

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Classification of the substance or mixture under OSHA’s Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0068037-01-4	1-Decene, homopolymer, hydrogenated	Yes	UVCB XU	ACTIVE
0064742-54-7	Distillates Hydrotreated Heavy Paraffin	Yes	Present	
0068649-42-3	PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS,	Yes	UVCB	ACTIVE

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepeco® is an affiliated brand
of Lubrication Engineers, Inc.



Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

SDS Revision Date

27 January, 2026

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

End of Document



Safety Data Sheet
710 Maximum Performance Synthetic ATF

SDS Revision Date:
27 January, 2026

Swepco® is an affiliated brand
of Lubrication Engineers, Inc.

