


Premium Food Grade Hydraulic Oil

Hydraulic systems in today's food, beverage, meat and poultry processing plants have to operate continuously at peak efficiency ... and with complete food safety in the event incidental food contact occurs. Achieving this goal requires a superior lubricant ... one that is thermally stable at both high and low temperatures, has excellent resistance to moisture and acidic conditions typical of food plants, protects critical parts from wear AND is USDA/NSF/Canada Health H1 Compliant. SWEPCO 755 Premium Food Grade Hydraulic Oil is the answer ... a pure food grade lubricant with unsurpassed performance.



KEY BENEFITS

- USDA/NSF/Canada Health H1 Compliant
- An extended life hydraulic oil for food grade applications
- Pure synthesized hydrocarbon base provides thermally stable performance over a wide temperature range
- State-of-the-art non-toxic additive package enhances oxidation resistance and anti-wear properties
- Protects pumps, actuators & circulating systems from scuffing, scoring, rust and corrosion
- Excellent resistance to moisture and acidic conditions common in food & beverage plants
- Outstanding lubricity reduces energy loads
- Compatible with most common seals & paint finishes

Get food safety and superior performance in one lubricant . . .



BOTTLING



PROCESS MACHINERY




CANNING

Maximize uptime and food safety with the superior lubrication of SWEPCO 755 Premium Food Grade Hydraulic Oil.

Feature	Benefit
Synthesized Hydrocarbon Base Stock	<ul style="list-style-type: none"> • Gives a more uniform viscosity over a wide temperature range • Improves resistance to high temperature oxidation • Superior thermal stability prevents "varnish" deposits • Better low temperature flow characteristics
Oxidation Inhibitor	<ul style="list-style-type: none"> • Reduces oil thickening and degradation • Helps prevent sludge, varnish and carbon deposits that result from oxidation
Anti-Wear Inhibitor	<ul style="list-style-type: none"> • Helps prevent metal-to-metal contact and insures longer gear & bearing life
Naturally Low Pour Point	<ul style="list-style-type: none"> • Superior low temperature performance
Seal Compatibility	<ul style="list-style-type: none"> • Prevents shrinkage of seals, elastomers, gaskets eliminating leakage and loss of fluid • Reduces potential maintenance expense of seal replacement • Reduces likelihood of food contamination • Recommend testing of compatibility with neoprene and low nitrile Buna N materials
Long Life	<ul style="list-style-type: none"> • Lengthens drain cycles and reduces maintenance labor and waste oil disposal costs
Lab Tec SM Fluid Analysis	<ul style="list-style-type: none"> • Can maximize equipment and lubricant life and pinpoint impending problems • Reduces waste
The Bottom Line	<ul style="list-style-type: none"> • Extends the life of expensive equipment • Conserves energy through better friction reduction • Increases the service life of the oil • Reduces waste oil disposal • Reduces labor costs through decreased and simplified maintenance • Reduces costly scheduled and unscheduled downtime • Multi-purpose formulation reduces inventory and lubrication errors

TYPICAL PHYSICAL PROPERTIES

ISO Grade.....	22.....	32.....	46.....	68.....	100.....
Viscosity, cSt @ 40°C.....	21.7.....	30.6.....	46.9.....	64.2.....	97.9.....
Viscosity, cSt @ 100°C.....	4.56.....	5.89.....	7.77.....	9.72.....	12.86.....
Viscosity Index.....	127.....	134.....	135.....	134.....	126.....
Flash Point, COC, °F (°C).....	450 (232).....	460 (237).....	481 (250).....	484 (252).....	489 (254).....
Pour Point, °F (°C), Max.....	-94 (-70).....	-67 (-55).....	-62 (-53).....	-50 (-46).....	-45 (-43).....
Color	Clear.....	Clear.....	Clear.....	Clear.....	Clear.....
Dielectric Strength, volts, ASTM D-877.....	>35.....	>35.....	>35.....	>35.....	>35.....



A Product of SPX Technology™.

... the cutting edge performance SWEPCO
Customers have come to expect.



Southwestern Petroleum Lubricants, LLC

Fort Worth, Texas • Phone: (817)332-2336 • Fax: (800)736-5823 • Web: www.swepcolube.com