



Section 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity 757 Premium Food Grade Gear & Bearing Oil
Alternate Names 757
Unique Formula Identifier

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Uses and Uses Advised Against See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Southwestern Petroleum Lubricants LLC
3401 Quorum Drive, Suite 360
Fort Worth, Texas 76137
Customer Service: 1+734 930-0009

1.4. Emergency telephone number

Emergency

24 hour Emergency Telephone No.

Polluxstraat 11 Telephone: +31 (13) 785 49 40
5047 RA Tilburg GSM: +31 (6) 150 230 19
The Netherlands E-mail: info@stratson.nl
Homepage: www.stratson.nl
SWEPCO lubes: www.swepcolube.com

Section 2. Hazard identification of the product

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]



Safety Data Sheet **SDS Revision Date:**
17/9/2024
757 Premium Food Grade Gear & Bearing Oil

2.2. Label elements

According to REGULATION (EU) 2020/878 amending Regulations EU 2015/830 and (EC) No 1907/2006

2.3. Other hazards

This product contains no PBT/vPvB chemicals.

This product contains no endocrine disrupting chemicals.

Section 3. Composition/information on ingredients

3.2. Mixtures

If the product contains substances that present a hazard according to Regulation (EC) No. 1272/2008 [CLP/GHS], they are listed below.

Ingredient/Chemical Designations	Weight %	EC No. 1272/2008 Classification	Notes
White mineral oil (petroleum) CAS Number: 8042-47-5 EC No. 232-455-8	65 - 85	Not Classified	
1-Decene, homopolymer, hydrogenated CAS Number: 68037-01-4 EC No. 500-183-1 REACH #: 01-2119486452-34	10 - 20	Asp. Tox. 1;H304	

^{^CLP 31} Reference EC No. 1272/2008 1.1.3.1. Notes relating to the identification, classification and labelling of substances (Table 3.1).

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eye Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed, obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents more than the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full-face piece and protective clothing. Persons without respiratory protection should leave the area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapor. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Section 7. Handling and storage



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.

7.3. Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
8042-47-5	White mineral oil (petroleum)	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	164.56 mg/m ³
		National	No Established Limit
68037-01-4	1-Decene, homopolymer, hydrogenated	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

8.2. Exposure controls

- Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes** Protective safety glasses recommended
- Skin** Avoid skin contact.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid
Color	Clear, yellowish fluid
Odor	None
Melting point / freezing point	No available information
Initial boiling point and boiling range	ASTM D 2882
Flammability (solid, gas)	No available information
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available information Upper Explosive Limit: No available information
Flash Point	270° C Open Cup ASTM D 93
Auto-ignition temperature	No available information
Decomposition temperature	No available information
pH	7.2
Viscosity (cSt)	No available information
Solubility in Water	Non-Emulsifier
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	No available information
Relative Density	0.82
Vapor Density	>5
Evaporation rate (Ether = 1)	Nil
VOC Content	None

9.2. Other information
 No other relevant information.





Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No available information

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and acids.

10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
White mineral oil (petroleum) - (8042-47-5)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	No data available.	No data available.
1-Decene, homopolymer, hydrogenated - (68037-01-4)	> 5,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available.	4,800.00, Rat - Category: NA	No data available.

Classification	Category	Hazard Description
Acute toxicity (oral)	---	---
Acute toxicity (dermal)	---	---
Acute toxicity (inhalation)	---	---
Skin corrosion/irritation	---	---
Serious eye damage/irritation	---	---
Respiratory sensitization	---	---
Skin sensitization	---	---
Germ cell mutagenicity	---	---
Carcinogenicity	---	---
Reproductive toxicity	---	---
STOT-single exposure	---	---
STOT-single exposure	---	---
STOT-repeated exposure	---	---
Aspiration hazard	---	---

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

This product contains no endocrine disrupting chemicals.

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l	3hr IC50 Bacteria mg/l	Biodegradability %
White mineral oil (petroleum) - (8042-47-5)	>100.00, Oncorhynchus mykiss	>100.00, Daphnia magna	>100.00, Pseudokirchneriella subcapitata	---	34.82
1-Decene, homopolymer, hydrogenated - (68037-01-4)	No data available.	No data available.	No data available.	---	15.00

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

No available information

12.4. Mobility in soil

No available information

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6 Endocrine disrupting properties

This product contains no endocrine disrupting chemicals.

12.7. Other adverse effects

No available information

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

	ADR/RID	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Regulated	Not Regulated	Not Regulated
14.2. UN proper	Not Regulated	Not Regulated	Not Regulated



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

Phosphorothioic acid, O,O,O-triphenyl ester (Use restricted. See item 3. (liquid))

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16. Other information

SDS Revision Date

17/9/2024

MSDS Revision Number

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - International Carriage of Dangerous Goods by Road (Accord Dangereux Routier)

CAS - Chemical Abstract Service

CLP - Classification Labeling and Packaging

DOT - Department of Transportation

EC50 - European Commission

EC50 - Half maximal effective concentration

ErC50 - The concentration of test substance which results in a 50 percent reduction in growth rate (ErC50) relative to the control within 72hrs exposure.

GHS - Globally Harmonized System

IARC - International Agency for Research on Cancer

IATA - International Civil Aviation Organization



Safety Data Sheet **SDS Revision Date:**
757 Premium Food Grade Gear & Bearing Oil **17/9/2024**

IC50 - The amount of a substance suspended in the air required to kills 50% of a test animals during a predetermined observation period.

ICAO - International Civil Aviation Organization

IMDG - International Maritime Dangerous Goods

IMO - International Maritime Organization

LC50 - Is the Lethal Concentration of a substance at which 50% of test animals die.

LD50 - Is the Lethal Dose at which 50% of the animals will be expected to die.

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PBT - Persistent, Bioaccumulative and Toxic Chemicals

PEL - Permissible Exposure Limit

REACH - Registration, Evaluation, Authorization and Restriction of Chemicals

RID - Regulations concerning the international carriage of dangerous goods by rail)

STEL - Short Term Exposure Limit

TWA - Time Weighted Average

vPvB - Very Persistent and very Bio-accumulative

WGK - Water Hazard Class

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

No applicable GHS categories. Classification

Justification

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

End of Document