

Section 1. Identification

Product identifier

Product Identity
Other means of identification

Food Machinery Grease (Aerosol) Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Lubricant

Details of the supplier of the safety data sheet

Company Name	Southwestern Petroleum Lubricants LLC 3401 Quorum Drive, Suite 360 Fort Worth, Texas 76137
Emergency	
24 hour Emergency	734 930-0009
Telephone No.	
Customer Service:	Emergency numbers call Chemtrec 24/7 USA and Canada 1- 800-424-9300 or 1-703-527-3887

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Flammable Gas, category 1; H220	Extremely flammable gas.
Aquatic toxicity (acute), category 3; H402	Harmful to aquatic life.
Aquatic toxicity (chronic), category 3;	Harmful to aquatic life with long lasting effects.
H412	
Simple Asphyxiant	May displace oxygen and cause rapid
	suffocation.



Label elements



Danger

H220 Extremely flammable gas.

H412 Harmful to aquatic life with long lasting effects. May displace oxygen and cause rapid suffocation.

[Prevention]:

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking. P273 Avoid release to the environment.

[Response]:

P377 Leaking gas fire - do not extinguish unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

[Storage]:

P403 Store in a well-ventilated place.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

May displace oxygen and cause rapid suffocation.



Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Propane CAS Number: 74-98-6 Synonyms: Propane	7 - 13	Flammable Gas, category 1;H220 Liquified Gas;H280 Simple Asphyxiant	No data available
Butane CAS Number: 106-97-8 Synonyms: Butane	7 - 13	Flammable Gas, category 1;H220 Liquified Gas;H280 Simple Asphyxiant	No data available

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

- **General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- **Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

OverviewEFFECTS OF OVEREXPOSURE: Overexposure may result in light-headedness, staggering gait, giddiness, and possible nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.



May cause eye and skin irritation. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, and eye disorders. Treat symptomatically. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full-face piece and protective clothing. Persons without respiratory protection should leave the area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions



Safety Data Sheet Food Machinery Grease (Aerosol)

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapor. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong acids and oxidizing materials See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value	
74-98-6	Propane	OSHA	1000 ppm, 1800 mg/m ³	
		ACGIH	(D) Simple Asphyxiant - (EX) Explosion hazard	
		NIOSH	TWA 1000 ppm (1800 mg/m ³)	
106-97-8	Butane	OSHA	No Established Limit	
		ACGIH	1000 ppm (EX) Explosion hazard	
		NIOSH	TWA 800 ppm (1900 mg/m ³)	



Exposure controls	
Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Avoid skin contact. Protective gloves recommended.
Engineering	Provide adequate ventilation. Where reasonably practicable this should be
Controls	achieved using local exhaust ventilation and good general extraction. If
	these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Safety Data Sheet Food Machinery Grease (Aerosol)

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State Color Odor Melting point / freezing point Initial boiling point and boiling range Flammability (solid, gas) Upper/lower flammability or explosive	White to pale white Aerosol/Foam White Solvent Odor No available information No available information Gas Lower Explosive Limit: No available
limits	information Upper Explosive Limit: No available
	information
Flash Point	No available information
Auto-ignition temperature	240C after solvent is evaporated
Decomposition temperature	No available information
рН	No available information
Viscosity (cSt)	NLGI #2 grease after solvent is gone
Solubility in Water	Insoluble in water

Swepco.

Safety Data Sheet Food Machinery Grease (Aerosol) SDS Revision Date: 10/21/2024

Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa) Relative Density Vapor Density	No available information No available information No available information
Evaporation rate (Ether = 1)	No available information

VOC Content

No available information 10%

Other information

No other relevant information.

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur. **Chemical stability** Stable under normal circumstances. **Possibility of hazardous reactions** No available information **Conditions to avoid** Do not expose to heat or store at temperature above 120°F. **Incompatible materials** Strong acids and oxidizing materials **Hazardous decomposition products** Oxides of Carbon

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Food Machinery Grease (Aerosol)

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Propane - (74-98-6)	No data available.	No data available.	658.00, Rat - Category: NA	No data available.	No data available.
Butane - (106-97-8)	No data available.	No data available.	658.00, Rat - Category: NA	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
74-98-6	Propane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit
106-97-8	Butane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed:

EFFECTS OF OVEREXPOSURE: Overexposure may result in light-headedness, staggering gait, giddiness, and possible nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause eye and skin irritation. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of



coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, and eye disorders. Treat symptomatically.

Section 12. Ecological information

Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Propane - (74-98-6)	49.90, Fish	69.43, Daphnia sp	19.37, Algae
Butane - (106-97-8)	49.90, Fish (Piscis)	69.43, Daphnia sp	19.37, Algae

Persistence and degradability

There is no data available on the preparation itself. **Bioaccumulative potential** No available information **Mobility in soil** No available information **Results of PBT and vPvB assessment** This product contains no PBT/vPvB/vPvM chemicals. **Other adverse effects** No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Food Machinery Grease (Aerosol)

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper	Not Regulated	Not Regulated	Not Regulated
shipping name			
Transport hazard	I DOT Hazard Class: Not	IMDG: Not Applicable	Air Class: Not
class(es)	Applicable	Sub Class: Not	Applicable
	Sub Class: Not Applicable	Applicable	Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: No; Special precautions for user

No available information

Section 15. Regulatory information

Regulatory The regulatory data in Section 15 is not intended to be all-inclusive, only Overview selected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0000106-97-8	Butane	Yes		ACTIVE
0000074-98-6	Propane	Yes		ACTIVE

Proposition 65 - Carcinogens (>0.0%):



To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

SDS Revision Date

10/21/2024

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.



Safety Data Sheet Food Machinery Grease (Aerosol)

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders

End of Document